

IN THE CLAIMS

Please amend the claims as follows:

1. *(currently amended)* A boot method for use in a mobile device having FLASH memory storing ~~boot instructions and~~ a key value and content comprising boot instructions stored in a security location, ~~having~~ an internal read-only memory storing boot program code and a predetermined security value, and ~~having~~ a serial port, execution of the boot program code stored in the read-only memory causing the mobile device to performing the steps of:

reading a key value from a security location in the FLASH memory, the key value being independent of the content of the FLASH memory;

comparing the key value to a predetermined security value stored in the internal read-only memory, the predetermined security value being independent of the content of the FLASH memory; and

depending on the result of the comparison of the key value to the predetermined security value, either polling the serial port for activity or jumping to the FLASH memory for execution of boot instructions stored therein.

2. *(original)* A boot method according to claim 1 wherein the polling is performed if the key value does not match the predetermined security value.

3. *(cancelled)*

4. *(original)* A boot method according to claim 2 further comprising the step of downloading code into internal SRAM located in the mobile device in response to a detection of serial port activity.

5. *(original)* A boot method according to claim 4 further comprising the step of executing an instruction in the downloaded code.

6. *(previously presented)* A boot method according to claim 1 wherein the predetermined

security value is stored in a BootROM located in the mobile device.

7. *(previously presented)* A boot method according to claim 1 wherein the step of reading is performed in response to a reset command.

8. *(currently amended)* A processor configured to communicate with internal read-only and FLASH memories of an apparatus for use in a mobile device having a serial port, the processor being configured to execute boot program code stored in a read-only memory for reading a key value from a security location in the FLASH memory, and for comparing said key value to a predetermined security value stored in the internal read-only memory wherein said predetermined security value and said key value are each independent of other content stored in the FLASH memory, and, depending on the result of the comparison of the key value to the predetermined security value, either polling the serial port for activity or jumping to the FLASH memory for execution of boot instructions stored therein.

9. *(currently amended)* An apparatus for use in a mobile device having a serial port, the apparatus comprising:

a FLASH memory storing ~~boot instructions and having a security location for storing a key value in a security location and further storing content comprising boot instructions, the key value being independent of the content~~;

an internal read-only memory storing boot program code for reading the key value and further storing a predetermined security value stored in the internal read-only memory, the predetermined security value being independent of the content of the FLASH memory; and

a processor configured to communicate with the internal read-only memory and the FLASH memory, the processor being configured to execute the boot program code to read the key value from the security location, to compare the key value to the predetermined security value, and, depending on the result of the comparison of the key value to the predetermined security value, either polling the serial port for activity or jumping to the FLASH memory for execution of boot instructions stored therein.

10. *(previously presented)* An apparatus according to claim 9 wherein the internal read-only

memory comprises a Boot Read Only Memory (BootROM).

11. *(cancelled)*

12. *(original)* An apparatus according to claim 9 further comprising a reset means in communication with the processor for initiating a reset process.

13. *(original)* An apparatus according to claim 9 wherein the processor compares the key value and said predetermined security value in response to initiation of a reset process.

14. *(previously presented)* An apparatus according to claim 9 wherein the internal read-only memory is located on an ASIC.

15. *(original)* An apparatus according to claim 9 wherein the processor is located on an ASIC.

16. *(original)* An apparatus according to claim 9 wherein the processor comprises a microcontrol unit connected to the serial port.

17. *(previously presented)* An apparatus according to claim 9 wherein the processor comprises a digital signal processor connected to the FLASH memory means.

18. *(currently amended)* A method for bootup of a computing device, the computing device comprising a serial port and internal memory comprising FLASH memory and a BootROM memory comprising BootROM code, the method comprising the steps of:

executing instructions stored in the BootROM code to read a key value from a security location in the FLASH memory, the key value being independent of other the contents of stored in the FLASH memory;

executing instructions stored in the BootROM code to compare the key value to a predetermined security value stored in the BootROM memory, the predetermined security value being independent of the other content stored in the FLASH memory;

on the condition that the comparison shows a match between the key value and the predetermined security value, executing instructions stored in the BootROM code to transfer execution to instructions stored in a boot location in the FLASH memory; and

on the condition that the comparison shows a mismatch between the key value and the predetermined security value,

polling the serial port for activity,

downloading new code into internal memory through the serial port in response to a detection of serial port activity, and

transferring execution to instructions in the new code.

19. *(previously presented)* A program product for a computing device, the program product comprising program code embodied in a program product media, the program product comprising program code operative to carry out the steps of Claim 18.

20. *(currently amended)* An apparatus for use in a mobile device having a serial port and an internal memory comprising FLASH memory and a BootROM memory comprising BootROM code, the apparatus further comprising a processor,

_____the BootROM code comprising instructions executable on the processor to:

_____read a key value from a security location in the FLASH memory, the key value being independent of ~~other~~the contents of stored in the FLASH memory;

_____the ~~BootROM code further comprising instructions executable on the processor~~ to compare the key value to a predetermined security value stored in the BootROM memory, the predetermined security value being independent of the other content stored in the FLASH memory;

_____the ~~BootROM code further comprising instructions executable on the processor~~, on the condition that the comparison ~~shows~~indicates a match between the key value and the predetermined security value, ~~to transfer processor execution to instructions stored in a boot location in the FLASH memory~~; and

_____the ~~BootROM code further comprising instructions executable on the processor~~, on the condition that the comparison shows a mismatch between the key value and the

predetermined security value, to

_____poll the serial port for activity,

_____download new code into internal memory through the serial port in
response to a detection of serial port activity, and

_____transfer processor execution to instructions in the new code.